

DESCRIPTION

PRODUCT COVERED:

USR, CNR - Component Terminal Block, Cat. Nos. PA27 and FV27, with or without Suffix H, with or without Suffix WP, **with or without suffix XA1F followed by alphanumeric suffixes.**

Cat. Nos. PA35, PA44, FV44 and PA67 each with or without Suffix WP.

Note - USR - Investigated for compliance with United States Standard - UL 1059, the Standard for Terminal Blocks, Third Edition.

CNR - Investigated for compliance with Canadian National Standard - C22-2 No. 158-1987, the Standard for Terminal Blocks, dated December 1987.

GENERAL CHARACTER AND USE:

These devices are open, multipole terminal blocks which, as indicated in this report, may be suitable for field and/or factory wiring.

RATINGS:

Cat. No.	Ratings	Copper Wire Only -	
		Wire Range AWG Copper Sol/Str	Screw Torque (in, lb)
PA27, -WP, -XA1F	300 V, 15 A	No. 14-18	8.0
FV27, -WP, -XA1F	600 V, 15.A	No. 14-18	8.0
PA35, -WP	300 V, 6 A	No. 18-20	3.0
PA44, -WP	300 V, 25 A	No. 10-14	8.0
FV44, -WP	600 V, 25 A	No. 10-14	8.0
PA67, -WP	300 V, 15 A	No. 14-18	8.0

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - For use only in products where the acceptability of the combination is determined by Underwriters Laboratories Inc.

CAT. NO. NOMENCLATURE:

*Example 1: PA44 WP
 1 2

1. Basic Construction:

* PA35, PA44, FV44, PA67

*2. Connector Body Variations:

WP - Provided with wire guard.

Without Suffix - Wire guard not provided.