




>> PA35

Pillar terminal block (12 poles)



Technical data

	IEC STANDARDS	AMERICAN STANDARDS
Ratings	450V - 24A	300V - 6A
Wire size	2.5 sqmm	20 ÷ 18 AWG (3.0 lb/in)
Working Temperat.	- 5 ÷ 125°C (short time 155°C)	23 ÷ 221°F
Plastic Material	Polyamide, UL94 V2, GWIT 775°C, GWFI 850°C	
Metal Parts	Cage insert made in nickel plated brass; M3 (0.5Nm) Captive screw made in zinc plated steel	
Accessories	PA52	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	CA02.00597	2.5 sqmm - 450V - 125°C	EN 60998-1; EN 60998-2-1
	E2677	2.5 sqmm - 450V - 85°C	EN 60998-1; EN 60998-2-1
	40021011	2.5 sqmm - 450V - 24A - 125°C	EN 60998-1; EN 60998-2-1 (VDE 0613)
		E76048 vol. 1 sec. 1	20 ÷ 18AWG - 300V - 6A - 105 °C

Dimensional drawing

I dati tecnici possono essere modificati senza preavviso. / The technical data can be subject to changes without notice.

