




# >> PA44

## Pillar terminal block (12 poles)



### Technical data

	IEC STANDARDS	AMERICAN STANDARDS
<b>Ratings</b>	750V - 41A	300V - 25A
<b>Wire size</b>	6.0 sqmm	14 ÷ 10 AWG (9.0 lb/in)
<b>Working Temperat.</b>	- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
<b>Plastic Material</b>	Polyamide, UL94 V2, GWIT 775°C, GWFI 850°C	
<b>Metal Parts</b>	Cage insert made in nickel plated brass; M3.5 (0.8Nm) Captive screw made in zinc plated steel	
<b>Accessories</b>	PA296 - PA228 - PA52 - PA197	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	CA02.00596	6.0 sqmm - 750V - 110°C	EN 60998-1; EN 60998-2-1
	E2670	6.0 sqmm - 750V - 85°C	EN 60998-1; EN 60998-2-1
	40020993	6.0 sqmm (rigid) / 4.0 sqmm (flexible) - 750V - 41A - 110°C	EN 60998-1 EN 60998-2-1 (VDE 0613)
		E76048 vol. 1 sec. 1	14 ÷ 10 AWG - 300V - 25A - 105°C

### Dimensional drawing

I dati tecnici possono essere modificati senza preavviso. / The technical data can be subject to changes without notice.

