




>> PA44 wp

**Pillar terminal block
with Wire Protector
(12 poles)**



Technical data

	IEC STANDARDS	AMERICAN STANDARDS
Ratings	750V - 32A	300V - 25A
Wire size	4.0 sqmm	14 ÷ 10 AWG (9.0 lb/in)
Working Temperat.	- 5 ÷ 110°C (short time 140°C)	23 ÷ 221°F
Plastic Material	Polyamide, UL94 V2, GWIT 775°C, GWFI 850°C	
Metal Parts	Cage insert made in nickel plated brass; M3.5 (0.8Nm) Captive screw made in zinc plated steel; Wire protector made in stainless steel	
Accessories	PA296 - PA228 - PA52 - PA197	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	CA02.00596	4.0 sqmm - 750V - 110°C	EN 60998-1; EN 60998-2-1
	E2670	4.0 sqmm - 750V - 85°C	EN 60998-1; EN 60998-2-1
	40020993	4.0 sqmm - 750V - 32A - 110°C	EN 60998-1
			EN 60998-2-1 (VDE 0613)
	E76048 vol. 1 sec. 1	14 ÷ 10 AWG - 300V - 25A - 105°C	UL 1059; C22-2 N.158-1987

Dimensional drawing

I dati tecnici possono essere modificati senza preavviso. / The technical data can be subject to changes without notice.

