




>> PA76

Pillar terminal block (12 poles)



Technical data

	IEC STANDARDS	AMERICAN STANDARDS
Ratings	750V - 57A	600V - 50A
Wire size	10.0 sqmm	18 ÷ 8 AWG (12 lb/in)
Working Temperat.	- 5 ÷ 125°C (short time 155°C)	23 ÷ 221°F
Plastic Material	Polyamide, UL94 V2, GWIT 775°C, GWFI 850°C	
Metal Parts	Cage insert made in nickel plated brass; M4 (1.2Nm) Captive screw made in zinc plated steel	
Accessories	PA297 - PA52	

Approvals	File Nr.	Ratings (sqmm/AWG - V - A - T)	Standard References
	CA02.00595	10.0 sqmm - 750V - 125°C	EN 60998-1
	E2675	10.0 sqmm - 750V - 85°C	EN 60998-1; EN 60998-2-1
	40020951	10.0 sqmm (rigid) / 6.0 sqmm (flexible) - 750V - 57A - 125°C	EN 60998-1; EN 60998-2-1 (VDE 0613)
	 US	E76048 vol. 1 sec. 5	18 ÷ 8 AWG - 600V - 50A - 105°C

Dimensional drawing

I dati tecnici possono essere modificati senza preavviso. / The technical data can be subject to changes without notice.

